

ASSEMBLY INSTRUCTIONS

SSOW4

IMPORTANT NOTES

The water can flow in many forms and patterns on any of the stainless steel water features. A sheer fall of water is possible but will never be constant. Please allow 2-3 days for the water to settle.

DO NOT expect the water to cover 100% of the feature, but remember the better you level your feature, the better the water coverage.

We have found by adding some non- biological washing liquid to the feature, it breaks the water surface and helps the water coverage.

If the water gives excessive splash, you can always use a piece of plastic sheet, to go a little wider than the base liner under the rocks.

Our water features are designed for outside use, but can be put indoors if required. The pump supplied may give of some noise if used in a confined space. We strongly advice you run the feature out doors first to monitor for splash while the feature settles in.

ASSEMBLY

1. Using the base liner, mark the ground area that needs to be cleared.
2. Place liner into the hole and spirit level to make sure you have a level base for your feature.
3. Looking at the base of your feature connect your pump ensuring that the cable is passing underneath the liner bracket
4. Bolt your feature into the liner using the higher holes in the side of the feature to the pivot hole in the liner frame. Using a spirit level, on the top edge of the feature, adjust the levelling bolts until the feature is level in both directions. (This may need to be done again in a few weeks once the ground has settled).
5. Place the pond pump into the liner and connect the pipework to the outlets on the pump. Run the cable of your feature to the nearest power point for your first test. We recommend that a qualified electrician carry's out all electrical work.
6. Fill reservoir with water.
7. If you want to take the acrylic sheet out or adjust it to help water flow, this can be done from the bottom of the feature.
8. Turn your feature on and check to see if you have your desired effect. Once satisfied switch off and add reservoir lid. Decorate the lid with stone, pebbles or rock to give the finish required. Your feature should now be ready for operation. Keep checking the water level over the next few days to see if there is any splashing causing water loss. If so remove any stones that may be causing this problem.

IMPORTANT!!!

If your feature is going to be free standing, then it must be secured to the ground. This can be done by adding 'L' brackets to the outer bolts to the ground.

Stainless surrounds can be pushed over base once fixed down.

